



Specification:

1. Material: PA66 UL94V-0:
2. Current rating:3.0A AC,DC
3. Voltage rating:250V AC,DC
4. Temperature range:-25℃to+85℃
5. Contact resistance:≤20mΩ
6. Insulation resistance:≥1000MΩ
7. Withstand voltage:1000V AC/minute

Part No	Pin	A	B	C	D
https://www.sunrom.com/m/5227	2	2.50	5.70	3.70	3.70
https://www.sunrom.com/m/5228	3	5.00	8.20	6.20	6.20
https://www.sunrom.com/m/5229	4	7.50	10.70	8.70	8.70
https://www.sunrom.com/m/5338	5	10.00	13.20	11.20	11.20
https://www.sunrom.com/m/5648	6	12.50	15.70	13.70	13.70
https://www.sunrom.com/m/5649	7	15.00	18.20	16.20	16.20
https://www.sunrom.com/m/5650	8	17.50	20.70	18.70	18.70
https://www.sunrom.com/m/5651	9	20.00	23.20	21.20	21.20
https://www.sunrom.com/m/5652	10	22.50	25.70	23.70	23.70
	11	25.50	28.20	26.20	26.20
	12	27.50	30.70	28.70	28.70
	13	30.00	33.20	31.20	31.20
	14	32.50	35.70	33.70	33.70
https://www.sunrom.com/m/7141	15	35.50	28.20	36.20	36.20
	16	37.50	40.70	38.70	38.70

PAR	XH 2.5mm Housing	
DWN		
CHKD		
APVD		
SCALE:1:1	UNIT:MM	
SIZE:A4	SHEET:1F1	REV:A